



# Texas Electronics, Inc.

The Gold Standard in Weather Instrumentation Since 1957

## Rain Gauge Tipping Bucket

## TR-525i Series Rainfall Sensor



### Description

The Texas Electronics, Inc. TR-525I Rainfall Sensor is a remote tipping bucket style rain gauge that measures the amount of liquid precipitation.

The Rain Gauge is a freestanding receptacle for measuring precipitation. It contains an open top, which allows rainfall to fall into the upper portion, which is called the collector. Collected water is funneled to a mechanical device (tipping bucket), which incrementally measures the rainfall accumulation and causes a momentary closure of a switch. As water is collected, the tipping bucket fills to the point where it tips over. This action empties the bucket in preparation for additional measurement. Water discharged by the tipping bucket passes out of the rain gauge with no need for emptying.

The TR-525I was designed to meet the need for a rugged and reliable rain gauge tipping bucket with high accuracy and low cost.

### Features & Benefits

- Interfaces to virtually all data acquisition systems
- Knife-edge collector optimizes rainfall catch
- Exceptional splash-out protection reduces wind errors
- Easy installation and maintenance
- Over 30 years in production
- Lightweight spun Aluminum Exterior
- Anodized aluminum collector for weather resistance
- Integral Bubble Level

### Specifications

Resolution:	0.01" English 0.2 mm Metric (optional)
Accuracy:	1.0% up to 2"/hr (50 mm/hr)
Collector diameter:	6.060" (154 mm) with knife-edge
Funnel depth:	6.4" (163 mm)
Splash out protection:	>2" (50 mm)
Operating Temp:	32 to 125° F (0 to 50° C)
Storage Temp:	-40 to 160° F (-40 to 70° C)
Humidity Limits:	0 to 100%
Weight:	2.5 lbs. (1.2 kg) 6 lbs. (2.7 kg) shipping
Height:	10" (255 mm)
Cable:	25', 22 gauge 2 conductor
Switch:	Momentary potted reed switch
Switch rating:	30 VDC @ 2 A, 115 VAC @ 1 A
Switch Closure Time:	135 ms
Bounce Settling Time:	0.75 ms
Pivot:	Hardened SS Jewel & Pivot
Bucket:	Black ABS injection molded
Level:	Integral Bubble Level
Warranty:	3 years

### Installation & Maintenance

Installation consists of attaching the three sensor support legs to a firm platform (such as our MB-525 Mounting Base). Pole mounting on the mast of a weather station is available by securing to the included side bracket.

Maintenance consists of routine cleaning of debris from the filter screen, and occasional calibration verification with our FC-525 Field Calibration Kit.

### Ordering Information

Model #	Description
TR-525I	Rain Gauge, 6.06" collector, English (Please specify for calibration of 0.2 mm/tip)

#### Optional Parts / Accessories

HOBO	Event Datalogger and Software
MB-525	Pole Mounting Base
FC-525	Field Calibration Kit
BB-525	Bird Repellent
HT-525	Heater, 120 VAC
Cable	Additional Cable

Texas Electronics, Inc.  
5529 Redfield Street • Dallas, TX 75235  
Tel.214.631.2490 • Fax.214.631.4218 • 800.424.5651  
[www.texaselectronics.com](http://www.texaselectronics.com) • email: [info@texaselectronics.com](mailto:info@texaselectronics.com)